

**Hazardous Location Centrifugal Belt-Drive Upblast Exhaust Ventilator**




Designed to exhaust air in commercial and industrial applications with potential flammable particles or fumes. Units include explosion resistant motor, aluminum wheel and aluminum rub ring.

- Aluminum backward inclined, nonoverloading centrifugal wheel design
- Maximum inlet air temperature: 300° F
- Sealed pillow block bearings
- Air handling quality bearings meet minimum of L10-100,000 hours




Dayton Electric Mfg. Co. certifies that the ventilators shown herein are licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.



A	B	C	D
22 in	24 7/8 in	25 1/8 in	17 3/8 in

**Performance Characteristics**



**Construction Features**

<b>Impeller Diameter (Typ.)</b>	13 1/4 in
<b>Impeller Type</b>	Backward Inclined Centrifugal
<b>Impeller Material</b>	Aluminum
<b>Max Inlet Temp</b>	300 °F
<b>Bearing Type</b>	Sealed Pillow Block
<b>Drive Package Description</b>	Drives By Others
<b>Warranty Length</b>	1 Year

**Air & Sound Performance**

Motor HP	Max BHP	Fan RPM	CFM @	0.000" SP	0.125" SP	0.250" SP	0.375" SP	0.500" SP	0.625" SP	0.750" SP	0.875" SP	1.000" SP	1.250" SP
1/4	0.26	1305	CFM	1790	1709	1629	1547	1458	1340	1201	1003	—	—
			Sones	14.6	14.3	13.9	13.5	13.0	12.0	11.5	10.8	—	—
1/3	0.35	1435	CFM	1968	1895	1822	1749	1671	1586	1479	1358	1198	—
			Sones	15.7	15.5	15.1	14.8	14.3	13.8	13.1	12.5	11.9	—
1/2	0.52	1645	CFM	2256	2192	2128	2065	2001	1933	1864	1778	1684	1455
			Sones	17.9	17.6	17.4	17.2	16.9	16.5	16.1	15.6	15.1	13.9

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.